



**SL 191 L P IX****12NC/Fx: F161512****GTIN (EAN) code:****8050147615126**

<b>DIMENSION</b>	<b>MEASURE</b>	<b>DIMENSION</b>	<b>MEASURE</b>
<b>WOODEN CABINET</b>		42. Min-max height of the aesthetical panel	0 mm
<b>OVERALL CABINET</b>		43. Min-max width of the aesthetical panel	0 mm
01. Height MIN Niche, including all required space for installation or ventilation (HMIN)	0 mm	<b>Built In - Free Standing - Decorative</b>	
02. Height MAX Niche, including all required space for installation or ventilation (HMAN)	0 mm	14. Indicates position of the user interface	-
03. Width MIN Niche, including all required space for installation or ventilation (WMIN)	0 mm	15. Height from bottom line hood to top line air outlet (HM)	0 mm
04. Width MAX Niche, including all required space for installation or ventilation (WMAN)	0 mm	16. Diameter air outlet (ØAO)	125 mm
05. Depth Niche, including all required space for installation or ventilation (DN)	0 mm	17. Indicates measure between center of air outlet hole and rear wall (DAOW)	85 mm
06. Indicates whether a ventilation opening is needed or not. Default is "Y"	- Y/N	18. Distance between hole and lateral product body end (DTHX)	0 mm
<b>Vent-shaft outgoing</b>		19. Distance between hole and back product body end (DTHY)	0 mm
07. Area MIN for outgoing ventilation (VC_O)	0	20. Wheelbase of holes (DTHW)	0 mm
<b>APPLIANCE</b>		<b>Only Free Standing - Decorative</b>	
<b>Overall Appliance</b>		21. 1st Chimney height (HCH1)	0 mm
01. Height MIN product body (HMIPB)	0 mm	22. 2nd Chimney height (HCH2)	0 mm
02. Height MAX product body (HMAPB)	133 mm	23. Width of the chimney (WCH)	0 mm
03. Height MIN product in ducting mode (HMIPD)	0 mm	24. Depth of the chimney (DCH)	0 mm
04. Height MAX product in ducting mode (HMAPD)	0 mm	<b>Hood - Hob combination</b>	
05. Height MIN product in recirculating mode (HMIPR)	0 mm	25. Height MIN between bottom hood and top electric hob (HMIHE)	500 mm
06. Height MAX product in recirculating mode (HMAPR)	0 mm	26. Height MIN between bottom hood and top gas hob (HMIHG)	650 mm
07. Width product (WP)	899 mm	<b>WOODEN CABINET - DOWNDRAFT</b>	
08. Depth product (DP)	513 mm	<b>Downdraft hood (also hob combination)</b>	
09. Depth product body (DPB)	410 mm	01. Worktop thickness (TW)	0 mm
10. Width product body (WPB)	0 mm	02. Indicates whether a protection tray against heat or contact ist needed. Default is "N"	- Y/N
11. Space in front, which is required to guarantee full operability. The most protruding part gives this dimension (RSF)	0 mm	03. Distance MIN from bottom line of appliance to protection tray (DIPT)	0 mm
12. Power cord positioning from the middle of product body (PCD)	0 mm	<b>Overlaying - Downdraft</b>	
13. Aesthetic thickness: glass, protrusion, etc. (AT)	0 mm	04. Front distance from cut-out to worktop end, overlaying installation with gas hob (WT_OG)	0 mm
27. Height of the air outlet	0 mm	05. Front distance from cut-out to worktop end, overlaying installation with electric hob (WT_OE)	0 mm
28. Width of the upper part of the body	0 mm	06. Rear distance from cut-out to wall/ furniture, overlaying installation (DIR_O)	0 mm
29. Width of the lower part of the body	0 mm	07. Lateral distance from cut-out to wall/ furniture, overlaying installation (DIL_O)	0 mm
30. Depth of the upper part of the body	0 mm	08. Width MIN cut out, overlaying installation (WMIC_O)	0 mm
31. Depth of the lower part of the body	0 mm	09. Width MAX cut out, overlaying installation (WMAC_O)	0 mm
32. Height of the upper part of the body	0 mm	10. Depth MIN cut out, overlaying installation (DMIC_O)	0 mm
33. Height of the lower part of the body	0 mm	11. Depth MAX cut out, overlaying installation (DMAC_O)	0 mm
34. Width of the back part of the product body	0 mm	12. Radius cut out, overlaying installation (RCO_O)	0 mm
35. Width of the front part of the product body	0 mm	13. Overlaying installation. Combination Modality	-
36. Width of the cut for perimetral panel	0 mm	<b>Flush mounted - Downdraft</b>	
37. Depth of the cut for perimetral panel	0 mm	14. Front distance from cut-out to worktop end, flush installation with gas hob (WT_FG)	0 mm
38. Width of the lights	0 mm	15. Front distance from cut-out to worktop end, flush installation with electric hob (WT_FE)	0 mm
39. Distance from perimetral panel cut to the edge of the product	0 mm	16. Rear distance from cut-out to wall/ furniture, flush installation (DIR_F)	0 mm
40. Depth at maximum height	0 mm		
41. Depth at minimum height	0 mm		

<b>DIMENSION</b>	<b>MEASURE</b>
17. Lateral distance from cut-out to wall/ furniture, flush installation (DIL_F)	0
18. Width MIN cut out, flush installation (WMIC_F)	0
19. Width MAX cut out, flush installation (WMAC_F)	0
20. Depth MIN cut out, flush installation (DMIC_F)	0
21. Depth MAX cut out, flush installation (DMAC_F)	0
22. Radius cut out, flush installation (RCO_F)	0
23. Width milling rabbet, flush installation (WMR_F)	0
24. Depth milling rabbet, flush installation (DMR_F)	0
25. Thickness milling rabbet, flush installation (TMR_F)	0
26. Radius milling rabbet, flush installation (RMR_F)	0
27. Flush installation. Combination modality	-

<b>DIMENSION</b>	<b>MEASURE</b>		
01. Width tube downdraft. Watch the detail drawing for the exact position of the dimension line (WTD)	0		mm
02. Depth tube downdraft. Watch the detail drawing for the exact position of the dimension line (DTD)	0		mm
03. Depth immersion. Underneath the bearing area of the appliance (DI)	0		mm
<b>Installation Space - Downdraft</b>			
04. Depth of immersion underneath the appliance (DIIA)	0		mm
05. Width installation area. Bottom box protruding elements (WIA)	0		mm
06. Depth installation area. Bottom box protruding elements (DIA)	0		mm
07. Offset X direction. This dimension is taken at MIN appliance height (OX)	0		mm
08. Offset Y direction. This dimension is taken at MIN appliance height (OY)	0		mm
<b>Appliance other</b>			
00. Name of the template to be used	HOOD	BI	MORAN